

Boiling point	100 °C		Glossmetre ISO 2813	Wet application
Coverage	min 10 m ² /l	23 °C	30-35 µ dry film thickness	Delivery viscosity
Solid content	15,6	120 °C/2 h	Oven ISO 3251	Delivery viscosity
Pendulum hardness	35	23 °C	Konig ISO 1522	Dry Film
Flexibility	min. 1 mm	23 °C	Erichsen Cupping Test ISO 1520	Dry Film
Bending strenght(n/mm2)	4,1	23 °C	SIST EN 1015-11	Dry Film
In can stability	± 10 KU		4 days at 49±3 °C in distilled water	Dry Film

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **Non applicable**

10. The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Tuluğ Kaya
Plant Manager

E.Engin Gokler
General Manager



DBS
İNŞ.TAAH.KİM.SAN.ve TİC.LTD.ŞTİ.
Atayazma Mahallesi Çarşınay. Sk.
Demirli Sit. A Blok Kat: 2 Kat: 2/100/IST
Tic Sic No: 271 049 160



Date : 26.06.2013