Essential Characteristics	Performance							Harmonized Testing Procedure
	1		2		3		Mean value	
Bending strength (N/mm^2)	5.5		5.8		5.8		5.7	EN 1015-11
Compressive strength (N/mm^2)	23.4	24.4	24.3	23.4	24.4	24.3	23.4	EN 1015-11

Essential Characteristics	Performance						Harmonized Testing Procedure
	1	2	3	4	5	Mean value	
Water absorption w ($kg/m^2h^{0,5}$)	0.135	0.118	0.095	0.074	0.115	**0.11**	EN 1062 - 3
Thickness of application d (mm)	7.9	7.7	7.2	10.2	6.8	**8.0**	EN 1062 - 3
Classification according to SIST EN 1062 - 3	**Class II (medium water absorption)** (0.1 < w < 0.5)						

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **Non applicable**

10. The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Tuluğ Kaya
Plant Manager

E.Engin Gokler
General Manager

DBS
İNŞ.TAAH.KİM.SAN.ve TİC.LİD.STİ.
Altayçeşme Mah.Bağdat Cd.Sanayi Sk.
Demirli Sit. A Blok No:6 DİLİ Maltepe/İST
Tel: 271 049 1603

Date : 26.06.2013