

Essential Characteristics	Performance at Wall Mix W						Harmonized Testing Procedure	
	1	2	3	4	5	Mean value		
Adhesive strength (N/mm ²)	1,5	1,3	1,1	1,5	1,2		1,3	EN 1015-12
Breaking point*	50 % b 50 % a	80 % b 20 % a	60 % b 40 % a	100 % b	100 % b		80 % b 20 % a	EN 1015-12

* b – Cohesive breaking in mortar

a – Adhesive breaking in the contact with the base

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **Non applicable**

10. The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Tuluğ Kaya
Plant Manager

E.Engin Gokler
General Manager

DBS
İNŞ.TAAH.KİM.SAN.VE TIC.İD.Şİ.
Ataycılar Mah.Bağcıbaşı Sok. No: 5/1 Sk.
Denizli Sit. A Blok No: 6 D: 1 Kat: 101
Denizli / TÜRKİYE T. 0711 049 1603

Date : 26.06.2013