

Essential Characteristics	Performance						Harmonized Testing Procedure	
	1	2	3	Mean value				
Bending strength (N/mm ²)	4,1	4,4	3,8	4,1			EN 1015-11	
Compressive strength (N/mm ²)	13,2	12,4	12,8	12,9	13,3	12,9	12,9	EN 1015-11

Essential Characteristics	Performance				Harmonized Testing Procedure
	1	2	3	Mean value	
Dry density (kg/m ³)	1260	1260	1260	1260	EN 1015-10

Essential Characteristics	Performance							Harmonized Testing Procedure
	1	2	3	4	5	6	Mean value	
Capillary water absorption coefficient C _m (kg/m ² min ^{0,5})	0,10	0,15	0,10	0,15	0,15	0,15	0,15	EN 1015-18

Essential Characteristics	Performance	Harmonized Testing Procedure
Water vapor diffusivity Λ (10 ⁻¹⁰ kg/m ² sPa)	1,742	EN 1015-19
Water vapor permeability W _{vp} (10 ⁻¹² kg/msPa)	3,833	EN 1015-19
Water vapor diffusion resistance coefficient μ	52	EN 1015-19

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **Not applicable**

10. The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Tuluğ Kaya
Plant Manager

E.Engin Gokler
General Manager

DBS
İNŞ.TAAH.KİM.SAN.ve TIC.LTD.ŞTİ.
Altaycaşme Mah. Bağdat Cd. Sarıyeri B.
Pamuk Sit. A Blok No: 6/101 Kat: 10/15
K: 34397 Üsküdar/İSTANBUL

Date : 26.06.2013