

In accordance with Annex III of Regulation (EU) No. 305/2011
(Construction Product Regulation)

For the product "**Flex C Ment – Wall Top Coat**"

1. Unique identification of the product-type:

Wall Top Coat "Overlay Mix" White

2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):

Batch number: See product and label

3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:

Screed materials with cement binder

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in Article 11 (5):

Flex-C-Ment™

DBS İnşaat Taah Kimya San ve Tic Ltd Sti

Altaycesme Mah Bagdat Cad Sanayi Sok No.6 Maltepe / Istanbul

Turkey

5. When applicable, the name and contact address of the authorized representative who has received a mandate for the tasks set out in Article 12(2):

Non applicable

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:

EN 13813 / System 4

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonized standard:

Manufacturer presents self-declaration according system 4 based on initial type test values issued by the following notified laboratory:

ZAG Ljubljana Slovenian National Building and Civil Engineering Institute

Dimičeva 12, 1000 Ljubljana, Slovenia

8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued:

Non applicable

9. Declared performance:

| Essential Characteristics | Performance | | | Harmonized Testing Procedure |
|---------------------------------------|-------------|------|-------------|------------------------------|
| | 1 | 2 | Mean value | |
| Consistency – flow table test (mm) | 180 | 181 | 181 | SIST EN 1015-3 |
| Dry bulk density (kg/m ³) | 1919 | 1921 | 1920 | SIST EN 1015-6 |
| Air bubble contents (vol.%) | 10,5 | 11,0 | 10,5 | SIST EN 1015-7 |

| Essential Characteristics | Performance | | | | | | Harmonized Testing Procedure | |
|---|-------------|------|------|------------|------|------|------------------------------|------------|
| | 1 | 2 | 3 | Mean value | | | | |
| Bending strength (N/mm ²) | 7,3 | 7,2 | 7,2 | 7,2 | | | EN 1015-11 | |
| Compressive strength (N/mm ²) | 42,2 | 43,4 | 44,8 | 47,6 | 46,8 | 49,9 | 46,0 | EN 1015-11 |

| Essential Characteristics | Performance | | | | | Harmonized Testing Procedure |
|--|--|-------|-------|-------|-------------|------------------------------|
| | 1 | 2 | 3 | 4 | Mean value | |
| Water absorption w (kg/m ² h ^{0,5}) | 0,320 | 0,226 | 0,177 | 0,320 | 0,28 | EN 1062 - 3 |
| Thickness of application d (mm) | 8,6 | 9,7 | 9,6 | 10,0 | 9,5 | EN 1062 - 3 |
| Classification according to SIST EN 1062 - 3 | Class II (medium water absorption) (0.1 < w < 0.5) | | | | | |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **Non applicable**

10. The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Tuluğ Kaya
Plant Manager

E.Engin Gokler
General Manager

Date : 26.06.2013