

According to 1907/2006/EC, Article 31

Reviewed On : 06.10.2015

Printing Date : 06.10.2015 Date of Preparation: 06-10-05 Prepared By: DBS LTD

#### **IDENTIFICATION OF SUBSTANCE**

Product details: Product Code FCMFLXEXTG Trade name: FLEX-C-MENTTM Flex Seal Extra Gloss Article Number: 00009 Application of the substance / the preparation: Water Based Acrylic Sealer for Extra Protection Manufacturer/Supplier DBS Insaat Taah Kimya San ve Tic Ltd Sti Akse Mah 471 Sok No.15 Cayirova / Gebze – KOCAELI /TURKEY Tel : +90 262 744 96 32 Fax : +90 262 744 27 14 e-mail : info@dekorbeton.com Emergency information: +90 262 744 96 32

# 1. DEFINITION:

Developed for mineral structured surfaces, water and pure silicon resin based penetrating sealer.

## 2. PROPERTIES:

Penetrates efficiently on all mineral based surfaces (i.e. concrete, mortar, auto claved- aerated concrete, and natural stone) and prevents capillary water absorption. While preventing accumulation of dirt, it also resists mildew and fungi growth on the surface.

## 3. USES:

As a protector sealer on natural stone to insure the longevity of historical restorations. It is also used to prevent water absorption on all mineral structured surfaces (cement based) which are exposed to water.

## 4. APPLICATION METHOD:

Apply without diluting with a brush or roller after removing all dust, dirt or old paint on the surface. For better protection re-apply a second coat as soon as the first coat is absorbed by the application surface. Note that the application of the second coat will result in a glossier surface.

## 5. TECHNICAL SPECIFICATIONS:

Appearance: Transparent – Mat Color: liquid Solids %: Minimum %25 weight percent – ISO 3251 Shelf life: Minimum 1year in original un-opened packaging Pendulum Hardness : 80 – ISO 1522 Adhesion : Gt-0 - ISO 2402

At C<sup>0</sup> room temperature. Viscosity : 80 KU – ISO 2431 Spec. Gravity : 1,02 gr/cm3 – ISO 2811 Flash Point: Non-Applicable Drying Time: 1 hr ISO 3678 Gloss Value : 80 - ISO 2813 Coverage : min 12m2/l on most surfaces Diluting Agent/ Ratio: Non- Applicable, Ready to use

#### **OTHER INFORMATION**

The data contained herein are furnished for information only and are believed to be reliable. However, DBS LTD does not assume responsibility for any results obtained by persons over whose methods DBS LTD has no control. It is the user's responsibility to determine the suitability of DBS's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of DBS's products. In light of the foregoing, DBS LTD specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of DBS LTD's products. DBS LTD further disclaims any liability for consequential or incidental damages of any kind, including lost profits.